



## Features

CalcoSlateStone is a highly flexible and seamless, mineral and emulsion based exterior texture coating material which can help realise a variety of finishes depending on the work person's skills.

This decorative and weather resistant texture finish is ideal for durable protection of wall surfaces and leaves behind a crack-free surface for long term use.

There are no added pigments or colorants, and the texture is used as a primary coat and then usually coloured over with a top coat after hardening. It is possible to request for special material to be used as a top coat.

### Key features include:



Seamless Application  
No joints\*



High Flexibility in Material  
Less cracks | Large panel sizes



High Adhesion to Substrate  
Less peeling off | High bonding



Thin Layer Application  
Environment friendly



No Requirement of Curing  
Less supervision required at site



Lower Dimensional Shrinkage  
Fewer cracks



High Strength  
High durability | Low maintenance cost



Easy to Clean  
Better looking surfaces



Quick Application  
Fast completion of project



Peace of Mind  
More value for money

## Application

Good for most walls, exteriors as well as interiors. Can be easily wrapped around wall edges, columns etc. High adhesion of the product makes it suitable for many diverse applications.

## Appearance

Supplied as a thick paste, ready to use. Slightly glossy after application. The material retains the surface texture formed during application.

## Specifications

### Max. Aggregate Size

3 mm

### Output/Coverage

~3-4 kg/ m<sup>2</sup> but may be more or less depending on application.

### Work Time

20 minutes. Will be less when temperature exceeds 28°C or humidity less than 50%

## Application Thickness

1-2 mm thick.

## Base Surface Preparation

The base wall surface should ideally be a well levelled mala plaster, clean and free of undue efflorescence, dust or any other material that may restrict adhesion. Cracks if any should be repaired. Any water proofing if required should be completed first. Any continuous source of water will leave the finish looking imperfect. The base must be consistent, without loose particles and disaggregation. Use suitable FreeForm Primer.

## Application/Installation Method

Apply 1 coat of suitable FreeForm Primer and allow to dry. Pigmented primer to match the colour of the selected stones can also be used.

Aluminium profiles can be used to obtain patterns if required. The profiles should be fixed beforehand and removed (if required) after slight hardening of the render to reveal patterns.

Mixing- The material is mixed by electrically operated hand mixer in the recommended ratio till complete homogeneity is achieved. Too much water will reduce sticking ability to the surface.

Trowel Application- The material is applied by trowel in a smooth and uniform coat in upwards motion in 2-3 mm thickness till the base is completely hidden. After about 20-30 minutes, when the surface has sufficiently hardened, smooth strokes of trowel for purpose of smoothening the applied texture must be applied without material.

When steel trowels are used, we recommend use of SS trowels as the material may be slightly acidic in nature.

Check that the material develops good adhesion and establish application procedure by doing a small sample or mock-up first before applying on entire surface.

## Curing

No curing is required. Material is touch dry in 1 hour, and full cure is 5-7 days after application. Material should be protected from dust for at least 24 hours after application.

## After Protection

No special care is required after installation, but usually, the same is painted over with a suitable paint.

## Packing

20 kg bag

## Shelf Life

6 months from date of packing before opening. Use within few hours of opening. Store carefully away from dampness and moisture. Material may be suitable for use after indicated life if lumping and aggregation has not happened. Suitability should be checked.

## Precautions

Should be stored away from water. Use materials from different packs to reduce chance of any shade variation. Keep WC ratio and Curing conditions consistent to reduce chances of shade variation.

## Green Certification



This product is GreenPro Certified and qualifies as Green Product by CII-Green products and services council.

## Technical Support

☎ 9374001415

✉ support@freeformbyvyara.in

### Disclaimer

Any recommendations for application techniques are based on experiences. It is advisable to adapt processing techniques and material quantities to the given local conditions and we refer in this context to our general terms of sale and delivery. Hairline crack formation or deformation by shrinkage on principle cannot be excluded with the offered system and thus are not considered as technical defect. Coloured products are exclusively produced from natural raw materials. Thus, colour deviations cannot be excluded. The printed colour may deviate from the original colour shade. Test areas are strongly recommended before usage/execution in larger areas.

### Health Precautions

This product contains cement and has an alkaline reaction with moisture/water. Adequately protect hands and eyes. In case of contact with eyes consult doctor immediately.

**Cementitious and Epoxy Floors | Wall Finishes | Tile Adhesives | Base Materials | Sealers | DIY**