



Features

Ready to use DIY pre-mixed high quality concrete material, all care taken—only water is to be added. Be assured of excellent setting and demoulding time and exceptional finish, characteristics much superior to regular concrete.

Key features include:



High Strength
High durability | Low maintenance cost



Lower Dimensional Shrinkage
Fewer cracks in concrete



High Workability
Fast completion of project



Water Repellence
Moisture ingress & stain protection



Low Requirement of Curing
Less supervision required at site



Peace of Mind
More value for money



Efflorescence Resistance
Better looks | Low maintenance cost



High Consistency of Material
Peace of mind



Extensively Tested at Factory
Quality assured

Application

- Home articles
- Planters, Table tops, Kitchen sink
- Small repair works
- Articles can be polished or subjected to secondary treatment

Appearance

Dry concrete mix with aggregates

Specifications

Max. Aggregate Size	Compressive Strength
10 mm	>35 N/mm ²
Flexure Strength	Bulk Density
>6.5 N/mm ²	~1450 kg/m ³
Wet Density	Water Requirement
~2200 kg/m ³	12-13% of weight
Work Time	
15 minutes—Make only as much quantity as you expect to use up in 15 minutes. Higher temperatures above 32°C or wind over 8km/hr can cause faster setting.	

Application/Installation Method

Please refer to separate sheet for guidance on application method.

Curing

No curing is required. Casted article may be lightly covered for about 2–3 hours to prevent quick drying out.

Grinding/Other Finish

All type of secondary finishes like grinding, polish, impregnation, sealing, shotblasting, brushing, antiquing etc., are possible on the articles casted.

Packing

25 kg bag

Shelf Life

Minimum 3 months from date of packing before opening. Use within few hours of opening. Store in dry conditions.

Precautions

Should be stored away from water. Use materials from different packs to reduce chance of any shade variation. Keep WC ratio and curing conditions consistent to reduce chances of shade variation.

Green Certification



This product is GreenPro Certificated and qualifies as Green Product by CII- Green products and services council.

Technical Support

☎ 9374001415

✉ support@freeformbyvyara.in

Disclaimer

Any recommendations for application techniques are based on experiences. It is advisable to adapt processing techniques and material quantities to the given local conditions and we refer in this context to our general terms of sale and delivery. Hairline crack formation or deformation by shrinkage on principle cannot be excluded with the offered system and thus are not considered as technical defect. Coloured products are exclusively produced from natural raw materials. Thus, colour deviations cannot be excluded. The printed colour may deviate from the original colour shade. Test areas are strongly recommended before usage/execution in larger areas.

Health Precautions

This product contains cement and has an alkaline reaction with moisture/water. Adequately protect hands and eyes. In case of contact with eyes consult doctor immediately.

Cementitious and Epoxy Floors | Wall Finishes | Tile Adhesives | Base Materials | Sealers | DIY