



## Features

The FreeForm Putty is an excellent water resistant base material for application on walls, which protects the surface and enables excellent finish of paints. The Skim coat plaster material is supplied in powder form and based on high quality hydrophobic polymers and carefully selected graded aggregates. It produces a fine final finish coat. It helps create a durable and stunning final painted wall.

### Key features include:



Lower Dimensional Shrinkage  
Fewer cracks in concrete



High Workability  
Fast completion of project



Low Requirement of Curing  
Less supervision required at site



Thin Layer Application  
Environment friendly



High Adhesion to Substrate  
Less peeling off | High bonding



Extensively Tested at Factory  
Quality assured



No Contamination  
Better performance



Water Repellence  
Moisture ingress & stain protection



High Consistency of Material  
Peace of mind

## Application

For most plastered surfaces in interiors and exteriors.

## Appearance

Single component premixed plaster powder- ready to use with addition of clean water.

## Specifications

Max. Aggregate Size	Compressive Strength
0.5 mm	>7.5 N/mm <sup>2</sup>
Flexure Strength	Bulk Density
>3.5 N/mm <sup>2</sup>	~1200 kg/m <sup>3</sup>
Output/Coverage	Water Requirement
~ 1.8 kg /mm/m <sup>2</sup>	~36-40%

## Application Thickness

We recommend coating the walls in two coats of 1-1.5 mm each.

To achieve an even finish, the material should be skimmed in even thickness. Good finishing saves costs and time in the final finish and it causes less waste.

## Base Surface Preparation

Base surface should be clean and free of dust grease and loose particles or any other material that may restrict adhesion. Any water proofing if required should be completed first.

## Application/Installation Method

Please refer to separate sheet for guidance on application method.

**Curing**

The covered surface should be cured with soft water every 6-12 hours from application for the first 2 days.

**Packing**

25 kg bag

**Shelf Life**

3 months from date of packing before opening. Use within few hours of opening. Store carefully away from dampness and moisture.

**Green Certification**

This product is GreenPro Certificated and qualifies as Green Product by CII- Green products and services council.

**Technical Support**

☎ 9374001415

✉ support@freeformbyvyara.in

**Disclaimer**

Any recommendations for application techniques are based on experiences. It is advisable to adapt processing techniques and material quantities to the given local conditions and we refer in this context to our general terms of sale and delivery. Hairline crack formation or deformation by shrinkage on principle cannot be excluded with the offered system and thus are not considered as technical defect. Coloured products are exclusively produced from natural raw materials. Thus, colour deviations cannot be excluded. The printed colour may deviate from the original colour shade. Test areas are strongly recommended before usage/execution in larger areas.

**Health Precautions**

This product contains cement and has an alkaline reaction with moisture/water. Adequately protect hands and eyes. In case of contact with eyes consult doctor immediately.

**Cementitious and Epoxy Floors | Wall Finishes | Tile Adhesives | Base Materials | Sealers | DIY**